

CRL



Light Engine and Driver Unit



Complete Unit



Trim



Housing


TECHNICAL SPECIFICATIONS:

- :: Efficacy: >89LM/W
- :: Rated Power: 18W
- :: Delivered Light Output: 1606LM
- :: CRI: Ra>80
- THD: <20%
- :: Power Factor: >0.9
- :: Life Span: 50,000 hours
- :: Mounting: Recessed
- :: Driver Efficiency: >87%
- :: Temperature Rating: Designed to operate in temperatures 113°F



Ordering Guide:

CRL6-27W-40K-H



LED COMMERCIAL RECESSED LIGHTS

CATALOG NO.	WATTS	COLOR TEMP	LUMENS	NOTES
CRL4-27W-30K	27W	3000K	1800LM	Complete unit (Light engine + Driver + Trim)
CRL4-27W-40K	27W	4000K	1900LM	
CRL4-27W-50K	27W	5000K	1950LM	
CRL-EGN-18W-30K	18W	3000K		Light engine and driver units for 6", 8", 10" (Pick a trim below)
CRL-EGN-18W-40K	18W	4000K		
CRL-EGN-18W-50K	18W	5000K		
CRL-EGN-27W-30K	27W	3000K		
CRL-EGN-27W-40K	27W	4000K		
CRL-EGN-27W-50K	27W	5000K		
CRL-EGN-40W-30K	40W	3000K		
CRL-EGN-40W-40K	40W	4000K		
CRL-EGN-40W-50K	40W	5000K		
CRL-EGN-54W-40K	54W	4000K		
CRL-EGN-54W-50K	54W	5000K		
CRL-TRM-6		6" LED Commercial trim only, 6 inches		Trims only (Pick an engine above)
CRL-TRM-8		8" LED Commercial trim only, 8 inches		
CRL-TRM-10		10" LED Commercial trim only, 10 inches		
CRL-HSG-4		4" LED Commercial housing only, 4 inches		Housing only (Pick an engine & a trim above)
CRL-HSG-6		6" LED Commercial housing only, 6 inches		
CRL-HSG-8		8" LED Commercial housing only, 8 inches		
CRL-HSG-10		10" LED Commercial housing only, 10 inches		

B20

LED COMMERCIAL RECESSED LIGHTS

