

**SL-D**  
DIMMABLE



28W



40W



20W



30W



**TECHNICAL SPECIFICATIONS:**

- :: Westgate's versatile Dimmable Flood Lights with motion sensor and photocell options
- :: Can be installed with any standard LED dimmers (TRIAC types)
- :: Mounts flush on wall or 4" round weatherproof box
- :: Housing: Die-cast aluminum with powder coat finish
- :: Cover type: clear lens
- :: CRI: 80
- :: Operating Temp: -4°F to 104°F
- :: Power factor: .90~.97
- :: Light beam angle: 120° (28W & 40W) - 100° (20W & 30W per head)
- :: Voltage: 120V AC 50/60Hz
- :: Suitable for Wet Locations, IP65
- :: 7-year warranty

**APPLICATIONS:**

- :: Ideal for doorway, pathway and alleys
- :: Great for use with optional motion sensors or photocell

MOTION SENSORS



**SL-PIR-WH**  
180°, 350W Max Load,  
Outdoor Motion Sensor  
(White & Bronze)



**SL-PIR-BZ**  
180°, 350W Max Load,  
Outdoor Motion Sensor  
(White & Bronze)



**SL-PC**  
UL-listed mini photocell  
for SL series security  
lights only



**LED SECURITY LIGHTS WITH OPTIONAL MOTION SENSOR OR PHOTOCELL**

CATALOG NO.		WATTS	LUMENS	COLOR TEMP	REPLACEMENT RANGE
BRONZE	WHITE				
SL-20W-50K-BZ-D	SL-20W-50K-WH-D	20W	1900LM	5000K	70~100 MH
SL-20W-30K-BZ-D	SL-20W-30K-WH-D	20W	1900LM	3000K	70~100 MH
SL-30W-50K-BZ-D	SL-30W-50K-WH-D	30W	2800LM	5000K	70~100 MH
SL-30W-30K-BZ-D	SL-30W-30K-WH-D	30W	2800LM	3000K	70~100 MH
SL-28W-50K-BZ-D	SL-28W-50K-WH-D	28W	3400LM	5000K	100~150 MH
SL-28W-30K-BZ-D	SL-28W-30K-WH-D	28W	3400LM	3000K	100~150 MH
SL-40W-50K-BZ-D	SL-40W-50K-WH-D	40W	4800LM	5000K	150~175 MH
SL-40W-30K-BZ-D	SL-40W-30K-WH-D	40W	4800LM	3000K	150~175 MH
SL-PIR-BZ	120V AC, 180°, 350W Max Load, OUTDOOR MOTION SENSOR (WHITE or BRONZE)				
SL-PIR-WH					
SL-HPIR-BZ	120V AC, 240°, 350W Max Load, OUTDOOR MOTION SENSOR (WHITE or BRONZE)				
SL-HPIR-WH					
SL-PC	120V AC, Optional Photocell Component for the above series security lights, Incl. WH & BR trims to match security light color				