A19LED206-6PK

CRI 80 5000K 480Lumens LED A19

The high performance LED A19 architectural form and versatility to make it an excellent choice for new construction or retrofit applications.

Performance

- LED A19 is designed to provide 25,000 hours of life
- Energy-saving & Super bright, saving 78% energy compared
- •UL, for Dry Location Use

Construction


• Aluminum for excellent heat dissipation

Installation

• Size:Φ2.36"(60mm)*H4.49"(114mm)










Elitco Lighting



Specifications

Specifications			
Category	Light Bulb	Individual Box Weight per Unit (LBS)	0.13
Shape	A19	Inner Package Length (Inch)	7.44
Bulb Base Type	E26	Inner Package Width (Inch)	4.92
Bulb Base Finish	NO	Inner Package Height (Inch)	5.43
Color Temperature	5000K	Inner Package Weight Per Unit (Lbs)	1.8
Beam Angle	300°	Inner Package Quantity	6
Finish	White		
CRI	80		
Average Life (Hours)	25000		
Estimated Yearly Energy Cost (11 ¢/Kwh)	0.78		
Life Based On 3Hrs/Day (Years)	22.83		
Product Length (Inch)	N/A	Lamp Type	LED A19
Product Width (Inch)	2.36	Bulb Shape	A19
Product Height (Inch)	4.49	Dry/Wet/Damp	Dry
Product Extension (Inch)	N/A	Energy Star	YES
Product Weight Per Unit (Lbs)	0.1	Power Factor	0.7
Dimmable	YES	Current	60mA
Watts	6.5W	Lumen/Watt	74
Watt Equivalent	40	Warranty (Year)	3
Lumens	480	DLC (Yes/No)	NO
Certification (UL/ETL/FCC)	UL	Input Voltage	120V/60HZ
Individual Box LENGTH (INCH)	2.38	Housing Material	Aluminum
Individual Box Width (INCH)	2.38	Lens	PC
Individual Box HEIGHT (INCH)	5.23	Led Type	Bridgelux 2835