


P20COB-8-D-30-35-6PK

CRI 80 3000K 620Lumens LED Reflector



The high performance LED PAR bulb.

Perfect for track and recessed light fixtures.

For commercial or home lighting applications

Easy to use - designed in traditional bulb shapes and fits easily into existing fixtures

Performance



- LED PAR bulb is designed to provide 25000 hours of life
- Energy-saving & Super bright, saving 85% energy compared with traditional halogen lamp
- UL compliant.

Construction

- Die-cast Aluminum for excellent heat dissipation
- Dimmable.

Installation

- Rated for indoor/outdoor use
- Suitable for damp locations.
- Can't be used in totally enclosed fixtures
- Not for use with emergency exit fixtures or emergency exit lights
- Size:Φ2.48"(63mm)*H3.35"(85mm)



Specifications

Category	Light Bulb	Inner Package Length (Inch)	8.27
Bulb Shape	PAR20	Inner Package Width (Inch)	5.7
Bulb Base Type	E26	Inner Package Height (Inch)	3.94
Bulb Base Finish	Chrome	Inner Package Weight Per Unit (Lbs)	2.45
Color Temperature	3000K	Inner Package Quantity	6
Beam Angle	35°		
Finish	Matte White		
CRI	80		
Average Life (Hours)	25000		
Estimated Yearly Energy Cost (11 ¢ /Kwh)	0.96		
Life Based On 3Hrs/Day (Years)	22.83	Lamp Type	PAR20
Product Length (Inch)	N/A	Dry/Wet/Damp	Damp
Product Width (Inch)	2.48	Energy Star	NO
Product Height (Inch)	3.35	Power Factor	>0.9
Product Extension (Inch)	N/A	Current	80mA
Product Weight Per Unit (Lbs)	0.34	Lumen/Watt	78
Dimmable	YES	Warranty (Year)	3
Watts	8W	DLC (Yes/No)	No
Watt Equivalent	50W	Input Voltage	120V
Lumens	620	Housing Material	Aluminum
Certification (UL/ETL/FCC)	UL	Lens	Plastic
Individual BoxLength (Inch)	2.64	Led Type	Epistar
Individual BoxWidth (Inch)	2.64		
Individual BoxHeight (Inch)	3.5		
Individual BoxWeight Per Unit (Lbs)	0.41		