

# R61730NDK-6PK

## 6" LED LOW PROFILE DISK LIGHT




Elitco Lighting



Direct LED replacement for 6" recessed incandescent. Save 80% in energy costs – 15 watt LED versus 90 watt BR20 – and eliminate multiple lamp replacements over the 50,000 hour rated life.

### Performance

- Use with most 4" "J-BOX".
- Dimmable with most standard incandescent (triac) and low voltage electronic (ELV) dimmers for 5-100% light control
- Eliminate up to 14 lamps replacements - long life Seoul LEDs last up to 50,000 hours, compared to incandescent lamps with a rated life of 2,500 hours
- Energy Star and ETL compliant, for use in wet locations



### Construction

- Aluminum trim ring with durable powder coat finish
- Polycarbonate lens diffuses light
- No LED DRIVER

### Installation

- Mount on standard 4" Junction box



### Specifications

Category	Disk light	Individual Box Weight Per Unit (Lbs)	0.62
Shape	Round	Inner Package Length (Inch)	10.39
Bulb Base Type	Integrated LED	Inner Package Width (Inch)	7.97
Bulb Base Finish	N/A	Inner Package Height (Inch)	8.5
Color Temperature	3000K	Inner Package Weight Per Unit (Lbs)	3.75
Beam Angle	105°	Inner Package Quantity	6
Finish	Matte White		
CRI	90		
Average Life (Hours)	50000		
Estimated Yearly Energy Cost (11 ¢ /Kwh)	1.99		
Life Based On 3Hrs/Day (Years)	45.66		
Product Length (Inch)	N/A	Lamp Type	LED downlight
Product Width (Inch)	7.32	Bulb Shape	N/A
Product Height (Inch)	1.18	Dry/Wet/Damp	Damp
Product Extension (Inch)	N/A	Energy Star	N/A
Product Weight Per Unit (Lbs)	0.46	Power Factor	0.95
Dimmable	Yes	Current	155mA
Watts	16.5	Lumen/Watt	55
Watt Equivalent	75	Warranty (Year)	5
Lumens	900	DLC (Yes/No)	NO
Certification (UL/ETL/FCC)	ETL	Input Voltage	120V
Individual Box Length (Inch)	7.9	Housing Material	Aluminum
Individual Box Width (Inch)	7.6	Lens	PC
Individual Box Height (Inch)	1.6	Led Type	Hongli