## **K54124UNKI-**

## 12DK

CRI 90 4000K 800 Lumens LED RETROFIT BAFFLE TRIM

Direct LED replacement for 4" recessed incandescent. Save 80% in energy costs – 12 watt LED versus 65 watt BR20 – and eliminate multiple lamp replacements over the 50,000 hour rated life.

#### **Performance**

- •Use with mos 4" recessed cans
- Dimmable with most standard incandescent (triac) and low voltage electronic (ELV) dimmers for 5-100% light control
- Eliminate up to 14 lamps replacements long life Hongli LEDs last up to 50,000 hours, compared to incandescent lamps with a rated life of 2,500 hours
- Energy Star and ETL compliant, for use in wet locations

#### Construction

- Aluminum trim ring with durable powder coat finish
- Polycarbonate lens diffuses light

### Installation

• Recessed mount into 4"housing. Includes medium base socket adaptor for easy retrofitting in 4" recessed housings.





Watt Equivalent

Lumens

Certification (UL/ETL/FCC)

Individual BoxLength (Inch)

Individual BoxWidth (Inch)

Individual BoxHeight (Inch)

Individual BoxWeight Per Unit (Lbs)



Title 24

65W 800

ETL


5.50


5.50 2.75


0.73


# Elitco Lighting by Elegant











LUMINOUS INTENSITY DISTRIBUTION DIAGRAM

Cr	ecific	ations
OI.	Jechic	auons

opecifications			
Category	RETROFIT		
Bulb Shape	Square		
Bulb Base Type	Integrated LED		
Bulb Base Finish	N/A		
Color Temperature	4000K		
Beam Angle	95°	Lamp Type	LED DOWNLIGHT
Finish	Matte White	Dry/Wet/Damp	Damp
CRI	90	Energy Star	NO
Average Life (Hours)	50000	Power Factor	>0.9
Estimated Yearly Energy Cost (11 ⊄ /Kwh)	1.45	Current	200mA
Life Based On 3Hrs/Day (Years)	45.66	Lumen/Watt	65
Product Length (Inch)	5	Warranty (Year)	5
Product Width (Inch)	5	DLC (Yes/No)	NO
Product Height (Inch)	2.5	Input Voltage	120V
Product Extension (Inch)	N/A	Housing Material	Aluminum
Product Weight Per Unit (Lbs)	0.77	Lens	Acrylic
Dimmable	YES	Led Type	HONGLI
Watts	12W		