

OPTIONS & ACCESSORIES

GAUGE PLATES

2-48" (51-1219mm)

Gauge plates are used to check ovality of the I.D. of pipelines. Typically used in either progressive pigging applications or new pipeline construction. Gauge plates are usually cut to 95% of pipe I.D., but can be custom made to any O.D.


Size	I.D. (in)	Weight (lbs)
2"	0.563	0.1
3"	0.563	0.2
4"	0.563	0.4
6"	1.063	0.8
8"	1.063	1.3
10"	1.063	2.0
12"	1.063	2.8
14"	1.063	4.0



2" - 14" Standard Plates

- 1/4" Thick
- Bevelled Edge
- Non-Slotted

Size	I.D. (in)	Bolt Circle Diameter (in)	# Holes
16"	8.750	11.00	8
18"	10.875	12.75	8
20"	10.875	13.50	12
22"	10.875	13.50	12
24"	14.125	16.50	14
26"	14.125	16.50	14
28"	16.125	19.50	16
30"	16.125	19.50	16
32"	20.125	24.00	24
34"	20.125	23.00	18
36"	20.125	25.00	22
38"	22.125	27.00	24
40"	22.125	26.00	24
42"	24.125	30.00	24
48"	32.125	36.00	24



16" - 48" Standard Plates

- 3/8" Thick
- Non-Bevelled
- Slotted

SIZING RINGS

Apache can manufacture Pig Sizing Rings to any customer supplied dimensions, quickly and cost effectively. Sizing Rings are used to slide over a worn used pipeline pig to be used as an indication that the pig needs to be replaced by the operator. These rings should not be used as a go-no-go and only part of the operators decision making process if the used pig needs to be discarded.



2" - 14" Sizing Rings

- No handles



16" - 48" Sizing Rings

- Four (4) handles

OTHER ACCESSORIES

Rattler



Transmitter Housing

Custom design for any transmitter

